Corfu on plate UEL24 71 By KARCHER DESIGN

- Lever model: ER24 Corfu
- Suits on 2 1/8" (54mm) hole and center to center 5 1/2" (140mm)
- Dimensions: 9 7/8" x 2 3/8" x ½" (250 x 60 x 12mm)
- Standard door thickness 2 1/8" (55mm) and 2 9/16" (65mm)
- Distance ring (UZ D2 71) required for 1 3/8" (35mm) to 1 3/4" (45mm)
- Passage latch with standard Backset 2 3/8" (60mm)
- Stainless steel T-strike plate with plastic dust cover
- Stainless steel strike plate with plastic cover
- Stainless steel latch face plate
- Entrance version and Patio Version: Dead bolt latch: adjustable with a backset of 2³/₈" (60 mm) and 2³/₄" - (70 mm)
- Entrance version: Solid Brass Cylinder with 5 pins and C keyway

Functions: Entrance door plate with single cylinder deadbolt and passage lever (LA), passage (PA), Full Dummy (DUM), Pation (PAT)

Special options

- UEZ D2 71 (Distance Ring): For door thickness $1\frac{3}{8}$ $1\frac{3}{4}$ (35 45 mm) a distance ring is required
- UZ2500 LS 71 Full Lip strike
- UZ2570 Passage Latch with 2 3/4" (70mm) backset

Finish: satin stainless steel (finish code 71)

Karcher article no .:

UEL 24 LA 71: Entrance set with lever Corfu UEL 24 PAS 71: Passage set with lever Corfu UEL 24 DUM 71: Dummy set with lever Corfu UEL 24 PAT 71: Patio set with lever Corfu

Dimensional detail:

